

# Technical data



	<b>48 XL</b>	<b>48 XL Intensive</b>	<b>48 XLc</b>	<b>48 XLc Intensive</b>
Tubes	48 x 120 W	48 x 180 W	48 x 120 W	48 x 180 W
Face tanner	-	-	Integrated	Integrated
Surface	Metallic effect	Metallic effect	Metallic effect	Metallic effect
Illuminated logo	●	●	●	●
Inside lighting	●	●	●	●
Illuminated exit sign	●	●	●	●
Adjustable body cooler: 1-2	●	●	●	●
All-around body cooling system	●	●	●	●
XL-Light 2 m technology	●	●	●	●
Digital timer display	●	●	●	●
Connection for external timer	●	●	●	●
Radio-preparation	○	○	○	○
Loudspeakers	●	●	●	●
Xsens	○	○	○	○
Lift	○	○	○	○
Changing room	○	○	○	○
Hour counter	●	●	●	●
Connection	400 V-50 Hz 3~N/PE	400 V-50 Hz 3~N/PE	400 V-50 Hz 3~N/PE	400 V-50 Hz 3~N/PE
Power	ca. 5.7 kW	ca. 9.8 kW	ca. 5.7 kW	ca. 9.8 kW
Fuses	3 x 16 A	3 x 20 A	3 x 16 A	3 x 20 A
Weight	350 kg	375 kg	350 kg	375 kg

● = standard, ○ = optional

Specifications are subject to change without notice.  
The devices shown sometimes include special equipment.

